



HIDE 48 200

APPEARANCE



DIMENSIONS



PRODUCT

Name	HIDE 48 200
Reference	HD-TL-00440034RF490-020
Color	BLACK/WHITE/RAL
Category	TRACK 48VDC

LIGHTING INFORMATION

Light source	LED
Luminous flux of the system	483 Lm*
Power values of the system	4.2 W*
Colour temperature	4000 K
Colour Rendering index	≥ 90
MacAdam Step	3
Light beam angle	34°
Light curve	DEEP
Efficacy	115 Lm/W*
Power factor	**
Dimming	1-10/DALI/ZigBee***
Driver	INCLUDED
Energy efficiency	A+
Horizontal rotation	NO
Vertical rotation	NO
LED lifespan	50.000h (L80B10)
Voltage, Frequency	48 VDC
Ripple ratio	≤ 1 %
Electrical insulation class	III
Power supply manufacturer	BVR
LED manufacturer	SAMSUNG

OTHER DATA

Ingress Protection	IP 20
Weight	230 g
Packaged weight	280 g
Packaging dimensions	219 x 65 x 65 mm
Materials	ALUMINIUM, STEEL, POLYCARBONATE

* Power, luminous flux and luminous efficiency do not include AC/DC power supply (sold separately), and may vary depending on its characteristic

** Depends on AC/DC power supply specifications (sold separately)

*** Control of luminaires by radiosignal via mobile app (additional equipment required)

