


# MOVIE DIF 48

## APPEARANCE



## DIMENSIONS



## PRODUCT

Name	MOVIE DIF 48
Reference	MN-TL-01230103RM290
Color	BLACK/WHITE/RAL
Category	TRACK 48VDC

## LIGHTING INFORMATION

Light source	LED
Luminous flux of the system	907 Lm*
Power values of the system	12.2 W*
Colour temperature	3000 K
Colour Rendering index	≥ 90
MacAdam Step	3
Light beam angle	103°
Light curve	COSINE
Efficacy	74 Lm/W
Power factor	**
Dimming	1-10/DALI/ZigBee***
Driver	INCLUDED
Energy efficiency	A+
Horizontal rotation	NO
Vertical rotation	180°
LED lifespan	50.000h (L80B10)
Voltage, Frequency	48 VDC
Ripple ratio	≤ 1 %
Electrical insulation class	III
Power supply manufacturer	BVR
LED manufacturer	SAMSUNG

## OTHER DATA

Ingress Protection	IP 20
Weight	350 g
Packaged weight	420 g
Packaging dimensions	240 x 130 x 43 mm
Materials	ALUMINIUM, STEEL, POLYSTYRENE

\* Power, luminous flux and luminous efficiency do not include AC/DC power supply (sold separately), and may vary depending on its characteristic

\*\* Depends on AC/DC power supply specifications (sold separately)

\*\*\* Control of luminaires by radiosignal via mobile APP (additional equipment required)

